EUROCAVE

5 YEAR WARRANTY

V-INSP-XS

Maturing cabinet
Built-in and Flush-fitted – Full Glass door
1-temperature

Sliding shelf (6 bottles)

ACMSIW
ACMSIB

CONFIGURATIONS

Premium Pack bottle capacity[1]
17
2 sliding shelves (+grid)

GENERAL FEATURES

	Full Glass door
Gross weight packaged (kg)	53
Empty net weight (kg)	46,2
Dimensions H x W x D (mm)	620-690 x 594[2] x 590
Dimensions in pack H x W x D (mm)	780 x 645 x 630

TECHNICAL FEATURES

REGULATION

- On/Off/Standby of the display button
- Electronic regulation
- Temperature setting range between 5°C and 20°C
- Electronic external display and settings
- LED screen
- Backlit capacitive keys
- Visual and/or sound alarms in case of:
  - Temperature dysfunction (sound and visual)
  - Hygrometry dysfunction (visual)
  - Sensor fault (sound and visual)
  - Hygrometry limit (visual)
  - Open door (sound and visual)
  - Need to replace charcoal filter (visual)
- Automatic defrost
- Frost protection thermostat (double protection)

HOT – COLD – INSULATION TECHNOLOGIES

Cold production:	• Static • Compressor R600a
Cords:	• CE/UK/AU/CH/US
Heat production:	• Heating element
Heat release:	• Automatic, adjustable threshold
Inner material:	• Stucco aluminum
Exterior coating material:	• HDF (High Density Fiber) melamine-faced panels
Insulation type:	• Injected polyurethane foam (59mm)

EQUIPMENT & ACCESSORIES

EQUIPMENT

- Reversible Full Glass door with soft close and door stop
- Inner lighting : light strip and 2 LED (3 options: permanent, open door, disabled)
- Charcoal filter
- 4 adjustable feet
- Humidity cartridge
- Lock

ACCESSORIES

- 2 sliding shelves with Mains du Sommelier, open / close locking notch, setting of the Main du Sommelier at the front of the shelf
- Total capacity: 17 bottles*
- 6 removable bottles identifiers per sliding shelf
- 1 erasable felt-tip marker
- 1 microfiber cloth
- 1 EuroCave key ring

ENERGY EFFICIENCY & CONSUMPTION

Cords	230V-50Hz (R600a)
Type of door	Full Glass
Energy efficiency class	A
Annual energy consumption AEc[3] (Kwh/year)	139
Useful volume (liters)	65
Sound emission (dB(A))	38
Ambient temperature range (°C)	12-35

[1] Traditional Bordeaux bottles
[2] With fillers
[3] Calculation based on the result obtained over 24 hrs in standard conditions (25°C / 77°F)

EUROCAVE

Installation diagrams



Built-in



Flush-fitted

Storage layouts



Premium
Pack